



Flexible product for airtight and vaportight bushings. ISOVER Vario® Bushing seals are designed to work seamlessly together with Vario® and VapoBlock - vapor barrier films. With Vario® bushings seals, HVAC installations that are coming through the vapor barrier can be sealed airtight.

Product description

ISOVER Vario® Bushing seals are made of flexible and long-lasting EPDM cellular rubber, to ensure the air and water vapor tightness of the bushings. Vario® Bushing seals are self-adhesive and their adhesive surface is protected with a protective film. There are five different pipe size available, size for the most common HVAC bushings (50-200mm) and the so-called "blind" bushing for ect. electrical cables.

Application

Vapor barrier sealing for HVAC and electrical pipes.

Installation

Make sure that the installation surface is clean, dry and dust-free. Seat the ISOVER Vario® Bushing seals.

in place at the bushing, remove the protective paper from the adhesive surface and at the same time press the seal to the surface. If necessary, secure with MultiTape SL tape. See details installation instructions in the Isover Airtightness brochure.

Packaging

ISOVER Vario® Bushing seals sales package 25 x 2 bags. Retail pack of 2 bags.



Handling and storage

When handling packaging and products, the packaging or the manufacturer's instructions for use must be followed.

Learn more

Saint-Gobain Finland Oy reserves the right to change the appearance and technical properties of the product when production technology changes and evolves.

